

VX2240w

22" WIDESCREEN LCD
WITH 4000:1 DYNAMIC CONTRAST (TYP)

Dynamically brilliant widescreen display.

ViewSonic's 22" VX2240w widescreen LCD delivers unparalleled performance with ULTRA-FAST VIDEO RESPONSE as fast as 2ms, 4000:1 DYNAMIC CONTRAST (typ) and SUPER-HD 1680X1050 RESOLUTION. Games, HD movies, videos and graphic-intensive applications have never looked better on your desktop. This Vista® premium certified widescreen display enhances productivity by allowing you to view two documents side by side or to work in two applications without toggling. Connect your game console, DVD player and other components through the DIGITAL (DVI-D) AND ANALOG INPUTS. The Kensington® security port provides theft deterrence and the OSD and power lock prevent unauthorized changes to your optimal screen settings.



1680x1050
SUPER HD

4000:1
Dynamic Contrast

ENHANCE PRODUCTIVITY AND ENTERTAINMENT

- > Full 22" viewable widescreen with 1680x1050 resolution
- > Fast ClearMotiv® video response
Video response as fast as 2ms enables digital HD broadcast-quality video.
- > 4000:1 dynamic contrast ratio (typ)
Provides for darker black levels and better overall front-of-screen performance.
- > Stylish slim-bezel design
The thin bezel lets you see more without taking up valuable desktop real estate. The high neck and floating head design accentuate the visual experience.
- > OptiSync® digital/analog inputs expand your connectivity
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > Amplified Impulse™
Advanced amplified impulse technology accelerates grayscale transitions for superior video and gaming.
- > OnView® controls for superior screen adjustability
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > Windows® Vista® approved
- > PC and Mac compatible
- > TCO '03 and ENERGY STAR® qualified



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

VX2240w

22" WIDESCREEN LCD WITH 4000:1 DYNAMIC CONTRAST RATIO



LCD	Type	22" Wide Color TFT Active Matrix LCD
	Display Area	18.7" horizontal x 11.7" vertical; 22.0" diagonal
	Optimum Resolution	1680x1050
	Contrast Ratio	1000:1 static (typ), 4000:1 dynamic (typ)
	Viewing Angles	170° horizontal, 160° vertical @ contrast ratio > 10:1
	Response Time	up to 2ms, gray-to-gray (typ); 5ms black-white-black (typ)
	Light Source	Long life, 40,000 hrs. (typ)
	Brightness	300 cd/m ² (typ)
VIDEO INPUT	Panel Surface	Anti-glare
	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D (with HDCP)
	Frequency	F _H : 24~82kHz, F _V : 50~75Hz
COMPATIBILITY	Sync	H/V separated (TTL), composite, sync-on-green
	PC	VGA up to 1680x1050 non-interlaced
CONNECTOR	Mac®*	G3/G4/G5 up to 1680x1050
	Analog/Digital	15-pin mini D-sub/DVI-D
POWER	Power	3-pin AC plug (CEE22)
	Voltage	AC 100~240V, 50~60Hz (auto switch)
ERGONOMICS	Consumption	38W (typ)
	Tilt	-5°/ +20°
CONTROLS	Basic	Power, 1, down, up, 2
	OnView®	Auto image adjust, brightness, contrast, input select (analog, digital), ViewMatch® color adjust (sRGB, 9300K, 7500K, 6500K-default, 5400K, user color-RGB), information (resolution, H. frequency, V. frequency, pixel clock, model number, serial number), manual image adjust (H. size, H. position, V. position, fine tune, sharpness, dynamic contrast, aspect ratio, response time), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
OPERATING CONDITIONS	Temperature	32~104°F (0~40°C)
	Humidity	10~90% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	20.1" x 17.0" x 8.8" (509mm x 431mm x 225mm)
	Physical without stand	20.1" x 14.0" x 2.4" (509mm x 354mm x 61mm)
WEIGHT	Net with stand	11.0 lb. (5.0 kg)
	Net without stand	10.0 lb. (4.5 kg)
	Gross with stand	14.0 lb. (6.4 kg)
REGULATIONS	UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, NEMKO/GS (covers TUV/GS), NEMKO ERGO (covers TUV/ERGO, ISO 13406-2 & MPR II), TCO'03, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, Argentina-S, Green Mark, RoHS, EPEAT-Silver	
RECYCLE/DISPOSAL	The lamp in this product contains mercury. Please dispose of in accordance with local, state and federal laws.	
POWER MANAGEMENT	Meets TCO'03 and ENERGY STAR® standards	
PACKAGE CONTENTS	LCD display, power cable, 15-pin VGA video cable, DVI cable, Quick Start Guide, ViewSonic Wizard CD	
WARRANTY	Three-year limited warranty on LCD, parts and labor	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13663-00B-09/07] VX2240w-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com